



SOFAR 20k~33kTL-G2

20000/ 25000/ 30000/ 33000

Three-Phase Dual-MPPT

4"

Super large 4-inch LCD

1100v

1100V voltage level design

DRM

Built-in DRM port and logic

98.6%

Max. efficiency up to 98.6%



I-V curve scanning function



Built-in SPD, over / under voltage, over current, over temperature, Anti-islanding and other multiple protections

Datasheet	SOFAR 20000TL-G2	SOFAR 25000TL-G2	SOFAR 30000TL-G2	SOFAR 33000TL-G2
Input (DC)				
Recommended Max. PV input power	26600Wp	33250Wp	39900Wp	43890Wp
Max DC power for single MPPT	13000W	16000W	18000W	20000W
Number of MPP trackers	2			
Number for DC inputs	2 for each MPPT	3 for each MPPT	3 for each MPPT	3 for each MPPT
Max. input voltage	1100V			
Start-up voltage	250V			
Rated input voltage	620V			
MPPT operating voltage range	230V-960V			
Full power MPPT voltage range	480V-850V	460V-850V	520V-850V	580V-850V
Max. input MPPT current	24A/24A	28A/28A	30A/30A	30A/30A
Maximun DC input short circuit current per MPPT	30A	35A	37.5A	37.5A
Output (AC)				
Rated power	20000W	25000W	30000W	33000W
Max. AC power	22000VA	27500VA	33000VA	36300VA
Max. Output current	32A	40A	48A	53A
Nominal grid voltage	3/N/PE, 220/380Vac, 230/400Vac, 240/415Vac			
Grid voltage range	310Vac-480Vac (According to local standard)			
Nominal frequency	50/60Hz			
Grid Frequency range	45Hz-55Hz/54Hz-66Hz (According to local standard)			
Active power adjustable range	0~100%			
THDi	<3%			
Power factor	>0.99 (adjustable +/-0.8)			
Performance				
Max efficiency	98.2%	98.4%	98.4%	98.6%
European weighted efficiency	98.0%	98.2%	98.2%	98.2%
Self-consumption at night	<1W			
MPPT efficiency	>99.9%			
Protection				
DC reverse polarity protection	Yes			
DC switch	Yes			
Protection class/ overvoltage category	I/III			
Safety protection	Anti islanding, RCMU, Ground fault monitoring			
ARPC	Anti reverse power controller (optional)			
Communication				
Power management unit	According to certification and request			
Standard communication mode	RS485, Wifi/Ethernet/GPRS(optional), SD card			
Operation data storage	25 years			
General Data				
Ambient temperature range	-25°C~+60°C			
Topology	Transformerless			
Degree of protection	IP65			
Allowable relative humidity range	0~100%			
Max. operating altitude	2000m			
Noise	<30dB	<45dB	<45dB	<45dB
Weight	37kg			
Cooling	Natural	Fan	Fan	Fan
Dimension	666*512*254mm			
Display	LCD display			
Warranty	5 years/ 7 years/ 10 years			
Standard				
EMC	EN 61000-6-2, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12			
Safety standards	IEC 61000-6-2, IEC 61000-6-3, IEC 61000-3-11, IEC 61000-3-12, IEC 62109-1/2, IEC 62116, IEC 61727, IEC 61683, IEC 60068(1,2,14,30), IEC 60255			
Grid standards	AS/NZS 4417, VDE V 0124-100, V 0126-1-1, VDE-AR-N 4105, CEI 0-21/CEI 0-16, EN 50549, G59, P.O. 12.3, RD1699, UTE C15-712-1, EN 50530, NB/T32004			